


Protect your hands when doing hazardous jobs with cut resistant collection for work and at home. A wide range of cut protection, EN388 levels A (minimum) to level F (maximum) and ANSI A1-A9 are available. These levels are determined by a cut performance standard testing machine, used in both American (ANSI) and European (EN388) markets.



EN388 Cut Level 3 (Coup Test)  
ANSI Cut A2 (F2992-15 test)



## 359 Stealth Stinger

### Features & Benefits

15gg Fine gauge HPPE, nylon, glass, and lycra shell. Lightweight polyurethane coated palm for a sure-grip. Snug-fitting knit wrist.


**Applications:** Construction, Industrial

**Sizes:** S, M, L, XL, XXL

**SKU:** 1223.000



EN388 Cut Level 5 (Coup Test)  
ANSI Cut A3 (F2992-15 test)



## 547 Van Goat

### Features & Benefits

ANSI/ISEA 105-16 CUT LEVEL A4. Premium P-aramid/polyester/glass liner for superior protection. Drivers style with ergonomic inset thumb for superior flexibility and comfort. Hard-wearing full-grain goatskin leather offers exceptional strength and dexterity.


**Applications:** Construction, Farm & Ranch, Gardening & Landscaping, General Purpose, Industrial

**Sizes:** M, L, XL, XXL

**SKU:** 1213.000



EN388 Cut Level 5 (Coup Test).  
ANSI Cut A4 (F2992-15 test)



## 357 Stealth Dog Fight

### Features & Benefits

HPPE composite fibre seamless knit shell. "Be safe, be seen" with hi-vis safety yellow. Sandy nitrile finish. Ergonomically formed. Extended snug-fitting knit wrist.


**Applications:** Construction, Industrial

**Sizes:** S, M, L, XL, XXL

**SKU:** 1223.063



EN388 Cut Level 5 (Coup Test)  
ANSI Cut A9 (F2992-15 test)



## 034ALY48 Gridlock

### Features & Benefits

Ultimate needlestick. Cut and puncture resistance. 4/8 Alycore configuration. Heavy duty microfibre palm. Palm patches snug-fitting shirred elastic wrist. Slip-on style cuff.

**Applications:** Construction, Forestry, Gardening & Landscaping, Industrial, Waste Management

**Sizes:** M, L, XL

**SKU:** 1223.300